

NRF6

超重型 抽吸/输送软管


- 管 壁：聚醚型聚氨酯，食品级
- 螺旋圈：不锈钢螺旋钢丝
- 壁 厚：约2mm
- 温度范围：-40℃至+90℃
短时间可达125℃



介质



特性



特性：
内壁光滑、弯曲灵活、耐磨耐腐蚀、耐油、无毒、无卤、无软化剂、
抗菌抗水解原材料符合FDA 21 CFR 177.2600和1782010标准
软管符合欧盟EU Regulations 1935/2004, 10/2011和1282/2011

应用：
用于磨损性较强的颗粒粉体物料输送
用于食品行业、医药行业、化学行业

物料号	内径 毫米/mm	外径 毫米/mm	正压 巴 (bar)	负压 巴 (bar)	弯曲半径 毫米/mm	重量 千克/米 (kg/m)	长度 米/m
NRF6-032	32	43	5.235	1.000	90	0.680	10/15
NRF6-038	38	49	4.475	1.000	104	0.790	10/15
NRF6-040	40	51	4.270	1.000	109	0.820	10/15
NRF6-045	45	56	3.825	1.000	129	0.910	10/15/20
NRF6-050	50	61	3.470	1.000	134	1.000	10/15
NRF6-051	51	62	3.200	1.000	134	1.020	10/15
NRF6-055	55	66	3.170	1.000	151	1.090	10/15
NRF6-060	60	71	2.920	1.000	156	1.180	10/15
NRF6-063	63	74	2.810	1.000	163	1.230	10/15
NRF6-065	65	76	2.705	1.000	169	1.270	10/15
NRF6-070	70	82	2.520	1.000	186	1.370	10/15
NRF6-075	75	87	2.360	1.000	195	1.460	10/15
NRF6-076	76	88	2.355	1.000	195	1.470	10/15



法企公众号



服务微信

网址: <http://www.mgwflex.com>
邮箱: zx@mgwflex.com market@mgwflex.com
地址: 广州市增城区宁西街创誉路74号平安硅谷A1栋4001-4004
No. 74 Chuangyu Road, Ningxi Street, Zengcheng District, Guangzhou, 4001-4004, building a 1, Ping an Silicon Valley

物料号	内径 毫米/mm	外径 毫米/mm	正压 巴 (bar)	负压 巴 (bar)	弯曲半径 毫米/mm	重量 千克/米 (kg/m)	长度 米/m
NRF6-080	80	92	2.220	1.000	205	1.550	10/15
NRF6-090	90	103	2.195	1.000	250	2.060	10/15
NRF6-100	100	113	1.980	1.000	272	2.270	10/15
NRF6-102	102	115	1.890	1.000	272	2.310	10/15
NRF6-110	110	123	1.805	1.000	300	2.480	10/15
NRF6-115	115	128	1.730	0.975	317	2.580	10/15
NRF6-120	120	133	1.660	0.930	330	2.690	10/15
NRF6-125	125	138	1.595	0.895	336	2.800	10/15/20
NRF6-127	127	140	1.565	0.860	336	2.840	10/15
NRF6-130	130	143	1.535	0.800	355	2.900	10/15
NRF6-140	140	153	1.430	0.745	400	3.110	10/15
NRF6-150	150	163	1.335	0.835	435	3.680	10/15
NRF6-152	152	165	1.305	0.700	435	2.720	10/15
NRF6-160	160	173	1.255	0.660	470	3.910	10/15
NRF6-170	170	183	1.180	0.640	600	4.150	10/15
NRF6-175	175	188	1.150	0.620	700	4.260	10/15
NRF6-180	180	193	1.120	0.560	830	4.380	10/15
NRF6-200	200	214	1.010	0.550	950	5.940	10/15
NRF6-203	203	216	0.955	0.495	950	6.020	10/15
NRF6-225	225	239	0.900	0.445	1175	6.650	10
NRF6-250	250	264	0.810	0.445	1300	7.350	2.5/5/10
NRF6-275	275	289	0.735	0.405	1453	8.070	2.5/5/10
NRF6-300	300	314	0.675	0.375	1575	8.780	2.5/5/10

依据要求可订制更多尺寸.



法企公众号



服务微信

网址: <http://www.mgwflex.com>
邮箱: zx@mgwflex.com market@mgwflex.com
地址: 广州市增城区宁西街创誉路74号平安硅谷A1栋4001-4004
No. 74 Chuangyu Road, Ningxi Street, Zengcheng District, Guangzhou, 4001-4004, building a 1, Ping an Silicon Valley