

TF 1-A

特氟龙导电直管

- 内管特性：聚四氟乙烯 (P. T. F. E) 耐高低温耐腐蚀抗老化，不粘
- 输送介质：强酸，强碱，石油，柴油，汽油，化工食品，医药，胶水等各种流体
- 颜色：红色，黑色，蓝色，乳白色，半透明等
- 温度：内管耐温-65℃-260℃



产品认证



特性：
低弯曲力，优良的耐化学性，提供各种金属材质的压接式接头
防静电导电内衬

物料号	规格 SPEC	外径 毫米/mm	内径 毫米/mm	壁厚 (mm)	工作压力 (bar)	爆破压力 (bar)
TF1-A	1*3	3	1	1	10.2	30.6
TF1-A	2*4	4	2	1	10.2	30.6
TF1-A	25*4	4	2.5	0.75	10.2	30.6
TF1-A	3*4	4	3	0.5	10.2	30.6
TF1-A	3*5	5	3	1	10.2	30.6
TF1-A	32*52	5.2	3.2	1	10.2	30.6
TF1-A	35*55	5.5	3.5	1	10.2	30.6
TF1-A	4*6	6	4	1	10.2	30.6
TF1-A	45*55	5.5	4.5	0.5	10.2	30.6
TF1-A	5*7	7	5	1	10.2	30.6
TF1-A	6*8	8	6	1	10.2	30.6
TF1-A	6*9	9	6	1.5	10.2	30.6
TF1-A	65*75	7.5	6.5	0.5	10.2	30.6
TF1-A	8*10	10	8	1	10.2	30.6
TF1-A	10*12	12	10	1	8.16	25.5
TF1-A	10*125	12.5	10	1.25	8.16	25.5
TF1-A	12*14	14	12	1	8.16	25.5



法宝公众号



服务微信

网址：<http://www.mgwflex.cn>
邮箱：zx@mgwflex.com market@mgwflex.com
地址：广州市增城区宁西街创誉路74号平安硅谷A1栋4001-4004
No. 74 Chuangyu Road, Ningxi Street, Zengcheng District, Guangzhou, 4001-4004, building a 1, Ping an Silicon Valley

物料号	规格 SPEC	外径 毫米/mm	内径 毫米/mm	壁厚 (mm)	工作压力 (bar)	爆破压力 (bar)
TF1-A	12*14	14	12	1	8.16	25.5
TF1-A	13*15	15	13	1	8.16	25.5
TF1-A	14*16	16	14	1	8.16	25.5
TF1-A	16*18	18	16	1	8.16	25.5
TF1-A	16*19	19	16	1.5	8.16	25.5
TF1-A	19*22	22	19	1.5	5.1	20.4
TF1-A	20*24	24	20	2	5.1	20.4
TF1-A	25*28	28	25	1.5	5.1	20.4
TF1-A	25*29	29	25	2	5.1	20.4
TF1-A	32*36	36	32	2	2	10
TF1-A	38*42	42	38	2	2	10
TF1-A	48*52	52	48	2	2	10

依据要求可订制更多尺寸



法金公众号



服务微信

网址: <http://www.mgwflex.cn>
邮箱: zx@mgwflex.com market@mgwflex.com
地址: 广州市增城区宁西街创誉路74号平安硅谷A1栋4001-4004
No. 74 Chuangyu Road, Ningxi Street, Zengcheng District, Guangzhou, 4001-4004, building a 1, Ping an Silicon Valley