

TF 2-A

特氟龙波纹导电弯管

- 内管特性：聚四氟乙烯 (P. T. F. E) 耐高低温，耐腐蚀，抗老化，不粘
- 输送介质：高温油，高温水，高温蒸汽，强酸，强碱，汽油，化工，食品，医药等各种流体
- 温度：内管耐温-65℃-260℃



产品认证



特性：
低弯曲力，优良的耐化学性，提供各种金属材质的压接式接头
防静电导电内衬更小弯曲半径.

物料号	规格 SPEC	外径 毫米/mm	内径 毫米/mm	工作压力 (bar)	爆破压力 (bar)	最小弯曲半径 (mm)
TF2-A	1/4	9.5	6.5	4	14	20
TF2-A	5/16	12	8	4	14	22
TF2-A	3/8	14.5	10	4	14	26
TF2-A	1/2	17.5	13	4	14	26
TF2-A	5/8	21.2	16	3	12	32
TF2-A	3/4	25.5	19	3	12	55
TF2-A	1	32	25	3	10	80
TF2-A	1-1/4	42	32	3	9	100
TF2-A	1-1/2	47	38	3	9	100
TF2-A	2	61	50	2	8	125



法宝公众号



服务微信

网址：<http://www.mgwflex.cn>
邮箱：zx@mgwflex.com market@mgwflex.com
地址：广州市增城区宁西街创誉路74号平安硅谷A1栋4001-4004
No. 74 Chuangyu Road, Ningxi Street, Zengcheng District, Guangzhou, 4001-4004, building a 1, Ping an Silicon Valley